












# 2K Topcoat textured

595 TPC-EPX						821 TPC-ACR						825 TPC-ACR					
2K Epoxid Topcoat						2K Acryl Topcoat						2K Acryl Topcoat					
St.	Zn	Al*	Pl.	O.P.	SG.	St.	Zn*	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.
																	
SC65-0731, SC65-0810						SC29-0863, SC29-0844, SC29-0823						SC29-0863, SC29-0844, SC29-0823					
SV32-0482						SV13-0732, SV13-0701, SV15-0339						SV13-0732, SV13-0701, SV15-0339					
satin glossy, for smooth and textured application, good chemical resistance, direct adhesion to many substrates (*adhesion depends on aluminum alloy)						satin glossy, for smooth and textured application, good weathering resistance, suitable for use on many plastics (*adhesion depends on alloy)						satin glossy, for smooth and textured application, very good sagging resistance, high film build possible					

## Explanation

Product	Product
Product name	product name
Substrate	St. Zn Al* Pl. O.P. S.U.
Compliance	   
Hardener	SC00-0000, SC00-0000
Thinner	SV00-0000, SV00-0000, SV00-0000
Remarks	satin glossy, smooth and textured application, very good sagging resistance, high film thicknesses can be applied (*adhesion depends on aluminum alloy)

Symbols	
	VOC compliant
	Corrosion classification acc. to DIN EN ISO 12944
	Airless / Airmix Application
	Low flame spread

[www.salcomix.com](http://www.salcomix.com)

Substrate	
St.	Steel
Zn	Zink
Al	Aluminium
Pl.	Plastics
O.P.	Old Paintwork
S.U.	Salcomix Undercoats