












1K Topcoat

309 TPC-AKD						320/321 TPC-AKD						328 TPC-AKD					
1K Alkyd Topcoat						1K Alkyd Topcoat						1K Alkyd Topcoat					
St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.	St.	Zn	Al	Pl.	O.P.	S.U.
																	
no hardener						no hardener						no hardener					
SV12-0360, SV13-0732, SV13-0701						SV12-0360, SV13-0732, SV13-0701						SV12-0360, SV13-0732, SV13-0701					
glossy, direct adhesion to steel						glossy/satin glossy, good appearance						satin glossy, high sagging resistance, can be applied with brush and roll, direct adhesion to steel					

Explanation

Product	Product
Product name	product name
Substrate	St. Zn Al* Pl. O.P. S.U.
Compliance	   
Hardener	SC00-0000, SC00-0000
Thinner	SV00-0000, SV00-0000, SV00-0000
Remarks	satin glossy, smooth and textured application, very good sagging resistance, high film thicknesses can be applied <small>(*adhesion depends on aluminum alloy)</small>

Substrate	
St.	Steel
Zn	Zink
Al	Aluminium
Pl.	Plastics
O.P.	Old Paintwork
S.U.	Salcomix Undercoats

Symbols	
	VOC compliant
	Corrosion classification acc. to DIN EN ISO 12944
	Airless / Airmix Application
	Low flame spread

www.salcomix.com